

Elevated Walkway – Floor Mount

GRW.ELEV.F600 – 600mm walkway width

GRW.ELEV.F900 – 900mm walkway width

GRW.ELEV.F1200 – 1200mm walkway width



Elevated Walkway - Floor Mount

Applications

- Safe access to in-ceiling air conditioning systems, heating, air ducts etc, or above plant and equipment. It can be mounted to roof purlins or concrete and is suitable for drop heights of up to 6000mm.

Advantages

- Safe and simplified ceiling access encourages regular preventative maintenance of ceiling mounted plant and equipment.
- Designed and manufactured in Australia

Technical Data

Material

- High grade structural aluminium.
- Fixing brackets and joining plates manufactured from profiled stainless steel plate, powdercoated.
- T-bolt manufactured from stainless steel with anti-seize coating.

Dimensions

- Walkway widths:
 - GRW.ELEV.F600 - 600mm
 - GRW.ELEV.F900 - 900mm
 - GRE.ELEV.F1200 - 1200mm
- Stair tread: 250 x 40mm.
- Handrail post extrusion: 58 x 38mm.
- Aluminium expanded mesh: 600 x 13mm.

Weight

- Overall system weight: approx. 70kg per lineal metre.

Fixings (refer to installation manual).

- T-bolt: M10 x 25
- Tek screw: 12g stainless steel

Rating

- Working load limit 2.5kPa

Compliance

Hart elevated walkways are designed to comply with Australian Standard AS1657:2018 and relevant statutory WHS Codes of Practice/Guidelines.

Testing

Testing and performance based on requirements of Australian Standard AS 1657:2018.

Warranty

10 years from date of purchase subject to correct installation, use and maintenance in accordance with manufacturer's specifications and recommendations.

Inspection & Maintenance

Recommended inspection and certification required every 3 years by competent person in accordance with manufacturer's specifications and requirements. (Refer installation manual)

Important Notes

Failure to supply and/or install proprietary product in accordance with above standards and codes, specifications and instructions voids complete system certification and/or warranty.

Technical Support

Hart Australia
1300 794 046
customercare@hart.au
www.hart.au